

Hand Placed Concrete Bagwork Solutions

Biodegradable and Water-Soluble Lined Bagwork



SoluForm



SoluForm bagwork is supplied pre-filled with a 32N dry mix concrete strength and in a range of bagwork forms, meaning that bagwork arrives to site ready filled and ready to use.

SoluForm have developed and patented a range of liners, for use inside traditional hessian/jute bags, for the placement of concrete in or around rivers.

Our bagwork product is factory filled; ensuring consistent and accurate quantities within each bag, and that the bagwork is clean and dust free. Depending on the grade of concrete, pre-filled bagwork is available with biodegradable liners, for placement below water level, or with water soluble liners for placement either above the waterline or away from the watercourse.



Advantages of Prefilled Bagwork

- Ready filled, eliminating the need for time consuming or labour intensive filling on site, and ready for use.
- Factory filled and lined to produce a clean, dust free finished bag.
- Each bag is machine weighed, ensuring a consistent size and shape to each block.
- Factory filling in a dry controlled environment also ensures a satisfactory shelf life of up to nine months for the bagwork product.
- Removes any Health and Safety concerns a contractor may have about filling bagwork themselves.



Our SoluForm pre-filled bagwork has been fully Carbon Neutral since 2019.

SoluForm's Pre-filled Hand Placed Bagwork

Biodegradable and Water-Soluble Lined Bagwork



SoluForm

SoluForm Underwater Bagwork

Available in
a 32N mix



- Supplied with a 32N dry-mix concrete within a biodegradable liner inside an outer biodegradable hessian bag ready to be placed directly into the watercourse.
- For placement of dry-mix concrete below water when combined with steelwork rebar pins.
- The liners biodegrade along with the hessian bags over time, leaving just the concrete block. No waste is placed into the watercourse.
- Our starch based bagwork is manufactured from natural, renewable and sustainable resources.
- Allows the placement of concrete in most cases without the requirement to dewater or divert the watercourse.
- 50 bags (1.0T) per pallet (suitable for 0.69m³ of bagwork), 20kg per bag.
- Clean and dust free product for placement of concrete in a watercourse.
- Typical finished block dimensions 500 x 250 x 100mm.
- Suitable for a range of uses including underpinning, scour protection, void filling, or the creation of below water parts to river walls or headwalls.

*UK Patent No GB2464669

*UK Patent Application No 1905855.1



www.soluform.co.uk



SoluForm - A division of Hoben International Ltd.
Brassington Works, Derbyshire, DE4 4HF, England
Head Office 01629 541066 Email sales@soluform.co.uk